



FS-1370DN

Black & White Printing Solution

ECONOMICAL. ECOLOGICAL. ECOSYS PRINTERS.

- Fast output speed of 37 pages per minute
- Crisp black & white prints
- Low Total Cost of Ownership
- Substantially reduce your operation and maintenance costs
- Eco-friendly long life consumables
- Kyocera ultra-reliable technology





FS-1370DN



FS-1370DN shown with 2 additional paper feeders for an 800 sheet paper capacity



Print your files directly from memory using the convenient USB Host Interface



Replace the long life toner container quickly and easily

Basic Specifications

Technology and Configuration	Kyocera ECOSYS® Black & White Network Printer
Pages Per Minute	Letter: 37; Legal: 30; A4: 35
Warm-Up Time	20 seconds or less from main power on, 15 seconds or less from sleep mode
First Print Out Time	7.0 seconds or less (EcoFuser off)
Resolution / Bit Depth	Fine 1200 Mode (1,200 x 1,200 dpi), Fast 1200 Mode (1,800 x 600 dpi), 600 x 600 dpi, 300 x 300 dpi
Memory	Standard 128MB, Upgradable to 1152MB via 144 pin DDR2 SDRAM DIMM, Standard CF Card Slot (Type 1)
Duplex Printing	Standard Duplex
Electrical Requirements	120V, 60Hz, 8.0A; 220V, 50/60 Hz, 4.2A
Dimensions / Weight	14.8"W x 15.5"D x 10.5"H / 26.5 lbs
Typical Energy Consumption (TEC)	2.839 KWh/week
Noise (ISO 7777/ ISO 9296) ¹	Printing: 55dB(A), Ready 30dB(A)
Safety Standards	This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard
Maximum Monthly Duty Cycle	50,000 Pages Per Month

Controller Specifications

PU / MHz	Embedded Power PC 440F5 / 500 MHz
PDL / Emulations	PRESCRIBE, PCL6 (PCL5c, PCLXL), KPDL (PS3)
Direct Print	PDF Direct Print
Fonts	93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 Bitmap font
Barcodes	45 barcodes (e.g. EAN8, EAN13, EAN128), PDF-417-1
Supported Client Operating Systems	Certified for Microsoft® Windows 7, Vista® 32/64-bit, Windows® 2000, Windows XP® 32/64-bit, Windows Server 2003 32/64-bit, Windows Server 2008 32/64-bit; Mac OS X v10.3.9, v10.4, v10.5, v10.6; Linux
Supported Network Operating Systems ²	Microsoft Windows 2000, Server 2003, XP, Windows 7, Vista, 2003 64-bit, XP 64-bit, Vista 64-bit (for Microsoft IPv6 compatible with Windows 2003, XP, and Vista); Novell 5.1 and later; Mac OS X v10.2.8, v10.3, v10.4, v10.5; Linux, UNIX
Printer Management	Command Center Web Interface, PaperTrail, PDF Direct Print, KMnet Viewer, KMnet Admin, KMnet for Accounting, Internet Printing IPP 1.0
Connectivity / Interfaces	Standard 10/100 Base TX, High Speed USB 2.0, USB Host Printing
Network Protocols ²	IPv6: HTTP, LPD, FTP, IPP, RawPort, ICMPv6, LLTD, SNMP, DHCPv6, SMTP, POP3, DNS, SNMPv1/v2c/v3, WSD IPv4: HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMP, DHCP, SMTP, POP3, SNMP, DNS, WINS, NetBIOS over TCP/IP, SNMPv1/v2c/v3, Apple Bonjour Compatible, IPPS, LLTD, WSD Etc.: IPX/SPX, NetWare (NDS/Bindery), AppleTalk, NetBEUI
Security	SSL/TLS (HTTPS, IPPS), SNMPv3, AH, ESP 802.1x authentication (EAP-PEAP, EAP-TLS), IPsec
Drivers	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Mini Driver, Windows® 64 Bit Drivers

Paper Supply

Standard Paper Sources	250 Sheet Drawer, 50 Sheet MPT
Standard / Maximum Paper Sources	2 / 4 including MPT
Standard Duplex	20 PPM Letter
Std/Max Paper Capacity	300 / 800 Sheets
Standard Drawer Paper Size / Weight	Letter, Legal, A4, A5, Oficio2, A6, B5, B6, Folio, Statement, Executive, Custom (4.13 x 5.83 to 8.5 x 14) / 16 - 28 lb Bond
MPT Paper Size / Weight	Letter, Legal, A4, A5, A6, B5, B6, Custom (2.76 x 5.83 to 8.5 x 14) / 16 lb Bond - 120 lb Index
Input Materials	Bond, Recycled, Labels, Card Stock, Coated, Postcards, Envelopes, Transparency, Labels, Letterhead, Preprinted, Pre-punched, Colored, Custom
Output Capacity	250 Sheets face down

Optional PF-100 Paper Feeder

Paper Capacity	250 Sheets
Paper Size / Weight	Letter, Legal, A4, A5, Oficio2, A6, B5, B6, Folio, Executive, Custom (5.83 x 8.26 to 8.5 x 14) / 16 - 28 lb Bond
Input Materials	Bond, Recycled, Letterhead, Preprinted, Pre-punched, Colored, Rough, Custom
Dimensions / Weight	14.8"W x 15.4"D x 3.9"H / 7.7 lbs

The FS-1370DN can be configured with up to 2 additional PF-100 Paper Feeders

Consumables

Black Toner	TK-172 Toner for 7,200 pages ³ (ships with 2,300 pages)
-------------	--

¹ Sound Pressure
² May require software from the NOS vendor or third-party vendor
³ In accordance with ISO 19752

Kyocera Mita America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted – and reducing landfill waste.

ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today. Visit our TCO Tracker at www.kyoceramita.com and start saving.



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA ©2010 Kyocera Mita America, Inc.

IC# 855D400263

