

Just The Facts



FS-C5025N

Small Workgroup/Workgroup Color Network Printer with standard 500 Sheet Paper Drawer plus 100 Sheet Multi-Purpose Tray. Standard 128MB RAM, upgradeable to 640MB, and optional 40GB HDD. Optional Duplex. Optional Paper Handling.

Technology

- **ECOSYS Technology**
- **Desktop Full Color/Monochrome System**
- **Imaging System:** Four Drum Tandem
- **Controller:** PowerPC750CXr 500 MHz
- **Print Resolution:** 600 x 600 dpi (Multi-bit)
- **Gradation:** 256 Levels
- **Maximum Monthly Volume:** 85,000 pages

Memory Management

- **Std/Max 100-Pin DDR RAM:**
 - 128MB /640MB
 - Optional 64/128/256/512MB RAM
- **One (1) KUIO Expansion Slot**
 - Optional 40GB HDD
- **Standard Compact Flash Slot**
 - Compact Flash (Type1)

Speeds and Productivity

- **Output Speed (Color/Mono):**
 - 22/22 Letter; 18/18 Legal
- **Warm up:**
 - Less than 68 seconds (From Sleep Mode)
- **First Print Out Time:**
 - 13.0 seconds or less for Color or Mono

Paper Handling

- **Standard/Maximum Paper Capacity:** 600/2,100
- **Standard 500 Sheet Paper Drawer**
 - Paper Size: LTR, LGL, Oficio2, A4, A5, B5, A6, Folio
 - Paper Weights: 16 - 28 lb Bond
 - Paper Types: Bond, Recycled, Thick
- **Standard 100-Sheet Multi-Purpose Tray**
 - Paper Size: Custom: 2.8" x 5.8" - 8.5" x 14"
 - Paper Weights: 16lb Bond- 110 lb Index
 - Paper Types: Bond, Recycled, Thick, OHP, Labels, Envelopes, High Quality
- **Optional Duplex**
- **Paper Output:** (Based on 20 lb Bond)
 - Face Down - 250 Sheets
 - Face Up - 100 Sheets (requires PT-301 Face Up Tray)

Connectivity & Interface

- **Standard Interfaces**
 - 10/100BaseTX EtherNet
 - Hi-Speed USB 2.0
 - KUIO LV Slot (1)
 - Optional IB-23 Secure NIC

Print Description Languages

- PDL/Emulations: PRESCRIBE
PCL 6 (XL, 5e, PJL)
KPDL3 (PS3)

Fonts

- 136 Fonts for KPDL
- 80 Outline Fonts for PCL XL/5e
- 1 Bitmap Font

Compatibility

- **Driver Support:**
 - KX Driver for Windows®
 - PPD for MAC
 - PPD for Linux/UNIX
 - Certified UNI Driver
 - Windows® 64-bit Drivers
- **Operating System Support:**
 - Windows® 95/98/Me/NT4/2000/XP/2003
 - Novell® 3.x/4.x/5.x/6.x
 - Mac OS 8.x/9.x/10.x
 - Unix-Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX
- **Supported Protocols:**
 - TCP/IP, IPX/SPX, AppleTalk, NetBEUI
- **Web Interface:** Kyocera Command Center
- **Utilities:** KM-NET Admin, KM-NET Viewer, KM-NET for Clients, PDF Direct Printing, KX SpoolCenter, KM-NET for Accounting, IC-Link, PRESCRIBE Utilities

Yields

- Toner Yields - based on 5% (see table)

| Toner | TK Item | Yield | Starter Yield* |
|---------|---------|-------|----------------|
| Cyan | TK-512C | 8,000 | 4,000 |
| Magenta | TK-512M | 8,000 | 4,000 |
| Yellow | TK-512Y | 8,000 | 4,000 |
| Black | TK-512K | 8,000 | 4,000 |

* Starter yield shipped with printer

- Maintenance Kit: 200,000 pages (MK-542)
- PM Schedule: 200,000 Pages

Other

- Dimensions: 13.6" W x 18.5" D x 15.2" H
- Weight: 55.2 lbs
- Power Requirements: 120V, 60Hz, 9.1A
- Energy Star Compliant
- RoHS Certified (EU Standard)

Quick Specifications for FS-C5030N/FS-C5025N/FS-C5015N

| Specification | FS-C5030N | FS-C5025N | FS-C5015N |
|---------------------------|----------------------------------|-------------------|-------------------|
| Letter Speed (Color/Mono) | 26/26 | 22/22 | 17/17 |
| Legal Speed (Color/Mono) | 21/21 | 18/18 | 14/14 |
| Network Interface | Standard | | |
| Duplex | Optional | | |
| Std./Max. Paper Capacity | 600/2,100 | | 600/1,100 |
| F POT | 12.0 sec. | 13.0 sec | 16.0 sec |
| Warmup (from sleep) | 80 sec. | 68 sec. | 80 sec |
| Std./ Max. Memory | 128MB/ 640MB | | |
| CPU Speed | 600MHz | 500MHz | 400MHz |
| Print Resolution | 600 x 600 dpi (Multi-bit 2 or 4) | | |
| Toner Yield (5%) | CMYK (each) 8K | CMYK (each) 8K | CMY - 4K K- 6K |
| Drum Type | Organic Photoconductor (OPC) | | |
| Drum/MK Yield | 200K | | NA |
| PM Schedule | 200K | | NA |
| Max. Monthly Volume | 100K | 85K | 50K |

FS-C5025N - Shown with three (3) optional PF-60 Paper Drawers and DU-301 Duplex Unit



FS-C5025N - Shown with one (1) optional PF-60 Paper Drawer and DU-301 Duplex Unit



FS-C5025N Page Speeds

Simplex Speeds

| | |
|---------------------|-------|
| Letter (Color/Mono) | 22/22 |
| Legal (Color/Mono) | 18/18 |

Duplex Speeds

| | |
|--------------------------|-------|
| Letter (Color/Mono) | 20/20 |
| Legal (Color/Mono) | 17/17 |
| Duplex Letter Efficiency | 91% |
| Duplex Legal Efficiency | 94% |

| Option | Item Code | Description |
|--------|------------|--------------------|
| PF-60 | 083DD3KX | 500 Sheet Drawer |
| DU-301 | 1203JZ0UN0 | Duplex Unit |
| PT-301 | 1202F40UN1 | Face Up Paper Tray |
| EF-310 | 1203KX0KL0 | Envelope Feed |
| IB-23 | 1503K00000 | Secure NIC |
| HD-ME5 | 855D200101 | 40GB HDD |



Kyocera's objective is to manufacture superior products with the lowest Total Cost of Ownership (TCO), and have little or no impact on the environment. Kyocera's ECOSYS® Technology provides customers with a printing solution that incorporates life-long consumables and the lowest cost per print.

The operating costs of traditional cartridge-based page printers can easily exceed more than three times the original purchase price during the life of the product. By utilizing Kyocera's proprietary ECOSYS® Technology, a user can typically recoup a printer's purchase price in one year or less.

For the latest specifications on this product, please visit <http://www.kmaconnect.com>

Just The Facts