



KM-2540

Document Imaging Solution

SERIOUS BUSINESS.
SERIOUS OUTPUT.™



- ▶ Fast Output Speed of 25 Pages per Minute
- ▶ Standard Copy; Optional Print and Fax
- ▶ Up to 2,200 Sheet Paper Capacity
- ▶ Standard Duplex
- ▶ 600 x 600 dpi Resolution
- ▶ Optional Paper Handling and Advanced Finishing
- ▶ Kyocera's Long Life Consumables

KM-2540 SPECIFICATIONS

BASIC SPECIFICATIONS:

Configuration:	Workgroup Multifunctional with Standard Copy and Optional Print and Optional Fax. Standard 500 x 2 Paper Drawers Plus 200 Sheet Multi-Purpose Tray. Standard Duplex. Optional Document Processor. Optional Finishing and Paper Handling.
Resolution:	600 x 600 dpi / 256 Levels, Fast 1200 Print Mode
Copier Memory:	Standard 64MB RAM, Upgradeable to 192MB
Magnification:	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, Plus 25-400% Zoom
Electrical Requirements:	120V, 60Hz, 9A
Dimensions:	22.4"W x 25.2"D x 30.2"H
Weight:	166 lbs
Max Monthly Volume:	80,000 Pages Per Month

OUTPUT SPEEDS:

Warm-Up Time:	Within 15 Seconds, Program During Warmup, Auto Start
First Copy Out / First Print Out:	4.7 Seconds
Pages Per Minute:	25 Letter, 12.5 Legal, 12.5 Ledger

PAPER SUPPLY:

Standard Paper Sources:	Dual 500 Sheet Drawers, 200 Sheet MPT, Auto Tray Selection / Switching, Add Paper While Running
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size:	5.5" x 8.5" - 11" x 17"
Std / Max Paper Capacity:	1,200 / 2,200
Paper Weight:	16 - 32 lb Bond via Paper Drawers, 12 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

DUPLEX UNIT:

Duplex Type:	Standard Embedded Stackless
Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	17 - 21 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

COPY FUNCTIONS:

Control Panel:	Touch Screen Interface
Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy:	Up to 999, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Interrupt Copy, Repeat Copy, Scan Once Print Many, Electronic Sort, Rotate Sort, 2 in 1, 4 in 1, Border Erase, Margin Shift, Continuous Scan, Eco Mode

PAPER HANDLING OPTIONS:

DOCUMENT PROCESSOR: DP-670

Type:	Reversing Automatic Document Processor (RADF)
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size Processing
Capacity:	75 Sheet RADF / 30 Letter Size Originals Per Minute
Paper Weight:	12 - 43 lb Bond
Dimensions / Weight:	22.1"W x 19.2"D x 5.0"H / 15.4 lbs

FINISHER: DF-730

Stack Capacity:	1,000 Sheets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	Single Position
Dimensions / Weight:	21.9"W x 20.7"D x 36.0"H / 55 lb

INTERNAL FINISHER: DF-670

Stack Capacity:	500 Sheets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 - 32 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	Single Position
Dimensions / Weight:	12.8"W x 17.8"D x 6.5"H / 17.7 lbs

DUAL PAPER DRAWERS: PF-670

Paper Capacity:	500 x 2 Sheets
Paper Weight:	16 - 32 lb Bond
Paper Size:	5.5" x 8.5" - 11" x 17"
Dimensions / Weight:	22.4"W x 24.4"D x 12.2"H / 55.2 lbs

CONNECTIVITY:

OPTIONAL NETWORK PRINT: PRINT SYSTEM (Y)

Controller:	Embedded PowerPC750/ 400 MHz Controller
Printer Memory:	Standard 64MB, Upgradeable to 576MB, Optional HDD, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e, 136 Outline Fonts for KPDL3, 1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP/2003/Vista
Novell® OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, High Speed USB 2.0
KUIO LV Expansion Slot (2):	IB-23 Secure NIC; Optional Printer HDD
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Drivers:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers
Utilities:	KMnet Admin, KM-NET Viewer, KM-NET for Clients, KM-NET for Accounting, PDF Direct Print
Web Interface:	Kyocera Command Center

OPTIONAL FAX: FAX SYSTEM (P)

Compatibility:	Super G3
Quick Scan Speed:	1.2 SPP
Transmission Speed:	Approximately 3 Seconds per page
Modem Speed:	33.6 Kbps with Auto Fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory:	Standard 4MB / Maximum 32MB
Additional Fax Features:	Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting

ADDITIONAL OPTIONS:

Job Separator (JS-670); Attachment Kit (AK-670); 32MB Fax Memory; 128MB Copier Memory; 512MB Printer Memory; Stand



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2007 Kyocera Mita America, Inc.
IC# 855D400109



www.kyoceramita.com