



Business Savvy. Fax Friendly.

PLAIN PAPER LASER FAX
KM-F1060

- High Volume Laser Facsimile
- Super G3 Modem/33.6Kbps
- 2.7 Second per Page Fax Transmission
- 0.7 Second Quick Scan Speed
- Fast 19 Pages per Minute Print Speed
- 250/800 Sheet Paper Supply (Std/Max)
- Standard 100 Sheet Document Processor
- QWERTY Keyboard
- Standard Windows® Graphical Device Interface (GDI) Printer
- Optional Network Scan/IFax

 **KYOCERA**
Document Solutions

KM-F1060 Specifications

BASIC SPECIFICATIONS:

Configuration:	High Volume Desktop Facsimile with a 33.6Kbps Modem. Standard 100 Sheet Document Processor, 250 Sheet Paper Cassette and Single Sheet Bypass. Standard Windows® GDI Printing. Optional Network Scan/IFax. Optional G3 Dual Line Expansion. Optional 550 Sheet Paper Cassette.
Compatibility:	ITU-T Group 3, ECM
Scanning Resolution:	Standard: 203 dpi x 98 lpi Fine: 203 dpi x 196 lpi Super Fine: 406 dpi x 391 lpi High Resolution: 600 x 600 dpi
Print Resolution:	Fax/Copy: 600 x 600 dpi Print: 600 x 600 dpi, 300 x 300 dpi
Fax Memory (Std/Max):	12MB/512MB
Memory Capacity (Std/Max):	720 pages/12,750 pages
Document Memory Backup:	Flash Memory
Coding System:	MH/MR/MMR/JBIG
Scanning Method:	Contact Image Sensor (CIS)
Print Method:	Monochrome Laser
Print Width (Max):	8.15"
Electrical Requirements:	120V, 50/60Hz
Dimensions:	17.7"W x 16.5"D x 17.6"H
Weight:	48.5 lbs

OUTPUT SPEEDS:

Modem Speed:	33.6Kbps w/ Auto Fallback
Transmission Speed:	Approximately 2.7 Seconds per Page
Pages Per Minute:	19 Letter

PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Cassette, Single Sheet Bypass
Drawer Paper Size:	8.5" x 11", 8.5" x 14"
Bypass Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14"
Paper Capacity (Std/Max):	250 / 800
Paper Weight:	16-28 lb Bond
Output Capacity:	150 Sheets

DOCUMENT PROCESSOR:

Type:	Automatic Document Feeder (ADF)
Acceptable Originals:	5.5" x 5.5" - 8.5" x 14"
Capacity:	100 Sheet ADF
Paper Weight:	14 - 28 lb Bond
Effective Scanning Width:	8.34"
Quick Scan Speed:	Standard: 0.7 Seconds Fine: 1.4 Seconds Super Fine: 2.8 Seconds

DUPLEX UNIT:

Paper Size:	5.5" x 8.5" - 8.5" x 14"
Paper Weight:	20 - 24 lb Bond

FAX FUNCTION:

DIALING CAPABILITIES:

One Touch Dialing Keys:	80
Program Keys:	80
Speed Dialing Codes (Std/Max):	200/920
Total Numbers Stored (Std/Max):	280/1,000
Group Dialing:	80
Other Dialing:	Auto Dial, Intelligent Redial, Automatic Redial, Last Number Redial, Directory Search Dial, Chain Dial, Alternative Number Dial, Pulse/Tone Dial, Off Hook Dial
Max Dialing Digits:	36

ADDITIONAL FAX FEATURES:

Driver:	PC Fax Driver (Network Fax requires IF-47 Scanner Kit)
Transmission/Reception:	Multi Access, Memory Transmission, Quick Memory Transmission, Deferred Transmission, Priority Direct Transmission, Job Reservation (Sending/Receiving), Batch Transmission, Multi-Station Transmission, Relay Transmission (SMTP), Auto Fax/Tel Switching, Polling, Continuous Polling, Deferred Polling, Substitute Reception, Memory Reception, Fax Forwarding, Broadcasting, Auto Reduction, Fixed Reduction, Verification Stamp, Duplex Reception, Distinctive Ring Detection (DRD)
Security Communication/Codes:	Fax Access Code (Fax Lock), Pin Code Access, Sub-Address Transmission, Department Code Access (50)
Journals/Lists:	Transaction Journal, Communication Journal w/Image, Directory Sheet, Department Code List, Auto Dial List, Fax Parameter List, Communication Reserve Report
Utilities:	Network Address Book Editor, PC Fax Software, Device Configuration Editor

COPY FUNCTION:

Continuous Copy:	Up to 999
Reduction/Enlargement:	71% - 141%
Additional Features:	Duplex Copy, Electronic Sort, Rotate Copy

STANDARD PRINT:

Print Memory :	32MB
Windows® OS Compatibility:	Windows® 98/Me/NT4.x/2000/XP
Connectivity / Interface:	Standard 10/100BaseTX, USB 1.1
Supported Protocol:	TCP/IP
Supported PDL/Emulations:	Windows® GDI
Print Resolution:	600 x 600 dpi
Driver:	GDI Driver for Windows®
Utilities:	Status Monitor
Additional Features:	Duplex Print, N-Up Printing, Scaling, Confidential Mailbox Printing (requires optional 256MB or 512MB SD Memory Card)

OPTIONAL CONNECTIVITY:

NETWORK SCAN/IFAX: IF-47 Scanner Kit

SCAN:

Type:	Monochrome Network Scanner
Resolution:	600 x 600 dpi, 300 x 300 dpi, 150 x 150 dpi
File Formats:	PDF, TIFF
Scan Speed:	1.1 Seconds per Page (150 x 150 dpi)
Connectivity:	Standard 10/100BaseTX
Scanning Features:	Scan to PC, Scan to E-Mail, Scan to FTP
Supported Protocols:	TCP/IP, SMTP, POP3, MIME, DHCP, LDAP, SNMP/MB
Utilities:	Document Manager, Document Viewer
Additional Features:	LDAP, File Name Entry

INTERNET FAX:

IFax Compatibility:	ITU-T T.37, IETF RFC 2305
Connectivity:	Standard 10/100BaseTX
Supported Protocols:	TCP/IP, SMTP, POP3, MIME
File Formats:	TIFF-FX

PAPER HANDLING OPTION:

PAPER DRAWER: PF-47

Paper Capacity:	550 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11" - 8.5" x 14"
Dimensions:	17.7"W x 17.9"D x 5.5"H

ADDITIONAL OPTIONS:

G3 Multi-Fax Board (MP-47) for Dual Line Fax, Handset (HS-47)

CONSUMABLES: TD-47

TD-47:	All-in-One Cartridge 5,000 Pages@ 5% Coverage*
---------------	--

* based on ITU-T No. 1 Chart in Standard Mode
KM-F1060 ships with one (1) full TD-47 Cartridge



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2005 Kyocera Mita America, Inc.

Item Code# 87166685



www.kyoceramita.com